

SET O-RING PER TENUTE ROTEN/UNITEN 3 EPDM/FPM

E1(7) - Y1(Y)

ROTEN®



EPDM - E1

Temperatura: -45° max +150°

Impiego: acqua, acidi, alcoli, acetati, vapore (no idrocarburi)

FPM - Y1

Temperatura: -30° max +180°

Impiego: solventi, acidi, idrocarburi (no acetati, chetoni, eteri)

Roten 3

ALBERO	EPDM		FPM	
d1	COD	€	COD	€
10	0105510	2,82	0105810	9,42
11	0105511	2,82	0105811	9,42
12	0105512	2,82	0105812	5,35
13	0105513	3,58	0105813	10,42
14	0105514	3,58	0105814	5,92
15	0105515	3,58	0105815	7,34
16	0105516	3,58	0105816	7,34
17	0105517	3,96	0105817	13,24
18	0105518	3,96	0105818	8,30
19	0105519	3,96	0105819	17,52
20	0105520	3,96	0105820	9,01
21	0105521	4,58	0105821	19,08
22	0105522	4,58	0105822	10,83
23	0105523	4,90	0105823	19,08
24	0105524	4,58	0105824	10,83
25	0105525	4,90	0105825	12,19
28	0105528	6,78	0105828	14,18
30	0105530	6,78	0105830	14,39
32	0105532	6,78	0105832	14,75
35	0105535	8,73	0105835	27,25
38	0105538	10,11	0105838	41,96
40	0105540	10,11	0105840	41,96

Uniten 3 A norme EN 12756

ALBERO	EPDM		FPM	
d1	COD	€	COD	€
12	0105412	3,23	0105612	5,53
14	0105414	3,61	0105614	7,02
16	0105416	3,61	0105616	8,27
18	0105418	4,24	0105618	8,83
20	0105420	4,24	0105620	9,73
22	0105422	4,58	0105622	11,22
24	0105424	4,58	0105624	11,40
25	0105425	5,22	0105625	12,86
28	0105428	6,79	0105628	14,18
30	0105430	7,13	0105630	15,11
32	0105432	7,13	0105632	32,45
35	0105435	8,73	0105635	44,12
38	0105438	10,11	0105638	73,93
40	0105440	10,11	0105640	73,93

NUOVA CODIFICA

Un set comprende tre guarnizioni: o-ring albero, o-ring rotante, o-ring stazionario