


CAPICORDA PREISOLATI AD INNESTO RAPIDO

0,25÷6 mm² - Ottone stagnato con bussola
antivibrante in rame

CE


FEMMINA ISOLATA



TUBETTO PVC AUTOESTINGUENTE

Colore	Sezione mm ²	AWG	Ø A per vite	B	C	L	pz	COD	€/pz
•	0,25÷1,5	22÷16	2,8X0,5	6	1,8	18	100	3307507	0,17
•	0,25÷1,5	22÷16	2,8X0,8	6	1,8	18	100	3307508	0,17
•	0,25÷1,5	22÷16	4,8X0,5	6	1,8	19,5	100	3307509	0,17
•	0,25÷1,5	22÷16	6,3X0,8	7,8	1,8	19,5	100	3307510	0,17
•	1,5÷2,5	16÷14	4,8X0,5	6	2,3	20	100	3307511	0,17
•	1,5÷2,5	16÷14	6,3X0,8	7,8	2,3	20,5	100	3307512	0,17
•	2,5÷6	12÷10	6,3X0,8	7,8	3,4	25	100	3307514	0,25


FEMMINA TOTALMENTE ISOLATA



TUBETTO PVC AUTOESTINGUENTE

Colore	Sezione mm ²	AWG	Ø A per vite	B	C	L	pz	COD	€/pz
•	0,25÷1,5	22÷16	6,3X0,8	7,8	1,8	20,5	100	3307522	0,21
•	1,5÷2,5	16÷14	6,3X0,8	7,8	2,3	22	100	3307524	0,24
•	2,5÷6	12÷10	6,3X0,8	7,8	3,4	26	100	3307526	0,28

CONNETTORI DI TESTA RICAVATI DA TUBO RAME



Colore	Sezione mm ²	AWG	B	C	L	pz	COD	€/pz
•	0,25÷1,5	22÷16	5	1,8	26	100	3307652	0,15
•	1,5÷2,5	16÷14	5,5	2,4	26	100	3307654	0,17
•	2,5÷6	12÷10	6	3,6	27	100	3307658	0,25