

PANEL FANS

AC 220 Volts Series



Fig. 1



Fig. 2

DIMENSIONS			m ³ /h	rpm	W	A	dB	Fig.	kg	CODE	€
HT	WDTH	THK									
80	80	25	0.7/0.9	2300	10	0.10	29/33	1	0.20	0401076	25,82
80	80	38	0.8/1	2300	13	0.12	31/35	1	0.30	0401071	29,59
92	92	25	0.9/1.1	2300	13	0.12	36/39	1	0.23	0401072	31,76
120	120	25	1.9/2.3	2200	19	0.09	43/50	1	0.34	0401073	31,97
120	120	38	2.7/3.3	2700	22	0.20	44/49	1	0.52	0401074	30,25
172	150	51	5.4/6.6	2800	32	0.23	50/45	2	1.00	0401075	59,01

GENERAL CHARACTERISTICS:

Made of black die-cast aluminium, non-inflammable polycarbon blades, fitted on ball bearings. Each fan is designed so that, when the motor is stuck, the windings do not burn out. Also the use of non-combustible material guarantees greater safety..

APPLICATIONS:

Cooling of control units, control panels, computers, etc.

TECHNICAL FEATURES:

Single-phase motor 220-230 V 50-60 Hz.
Working temperature -20°C to +80°C