

VENTILATING BOXES SOUNDPROOFED

Unobox



MODEL	A	B	C	D	DI	A	B	m³/h	V	POLES	CODE	€
UNO 50-355	500	500	450	365	224	409	435	3100	230V	4	0411810	1150,00
UNO 67-400	670	670	620	404	253	579	605	4000	400V	4	0411812	1350,00
								4000	230V	4	0411814	1300,00
UNO 67-450	670	670	620	454	286	579	605	5500	400V	4	0411815	1414,00
								5500	230V	4	0411817	1400,00
UNO 67-500	670	670	620	504	321	579	605	9500	400V	4	0411818	1500,00
								6500	400V	6	0411819	1350,00
								6000	230V	6	0411820	1300,00
UNO 80-560	800	800	720	570	361	659	698	12000	400V	4	0411821	1950,00
								9000	400V	6	0411822	1800,00
UNO 80-630	800	800	720	634	407	659	698	12000	400V	6	0411823	2350,00
UNO 102-710	1020	1020	940	718	438	879	918	19000	400V	6	0411825	2900,00
								19000	400V	6	0411826	2900,00

tion units are of a backward curved blade type with the aluminium impeller keyed into the flange of the rotor of a motor with an external Rosenberg rotor.

CHASSIS

- Loadbearing structure in double chamber aluminium profiles, and aluminium angle profiles.
- Panelling 20 mm thick, with the double layer of galvanised steel plating, insulated using flameproof glass wool, which provides sound-

proofing and insulation.

DIRECTION OF ROTATION

The standard direction of rotation in the fans is to the right (seen from the intake side). If it rotates in the incorrect direction (blade curved forward, for example) there is a serious risk of overloading the motor. The correct direction of rotation must therefore be checked at the time of starting up.

MECHANICAL SEALS

PUMPS

FANS

MOTORS

INSULATION

EQUIPMENT

MOTOR SPARES

TOOL SPARES

SWITCHES