

SINGLE-PHASE MOTORS

2-POLE

Insulation class F, 230V



KW	HP	TYPE	Ø SHAFT	I	I.C.C.	η%	R.P.M.	COS. φ	CONDENS. 450V	MP/MN	KG	SHAPE	CODE	€
0,18	0,25	63	11	1,3	2,9	60	2750	0,98	10	0,75	4,5	B3	BM632025B3	98,31
												B5	BM632025B5	100,34
0,25	0,33	63	11	1,9	4,2	60	2750	0,98	14	0,7	5	B3	BM632033B3	99,18
												B5	BM632033B5	103,53
0,37	0,5	71	14	2,3	7,2	60	2780	0,98	14	0,7	7	B3	BM712050B3	112,70
												B5	BM712050B5	118,34
0,55	0,75	71	14	3,3	9,5	60	2780	0,98	12.5	0,7	7.5	B3	BM712075B3	120,38
												B5	BM712075B5	126,42
0,75	1	80	19	5	19,8	62	2750	0,99	31.5	0,92	10	B3	BM802100B3	165,59
												B5	BM802100B5	173,46
1,1	1,5	80	19	7,5	26,8	71	2750	0,97	35	0,88	11	B3	BM802150B3	170,52
												B5	BM802150B5	177,70
1,5	2	80	19	9,3	29,4	73	2750	0,98	40	0,66	12	B3	BM802200B3	173,13
												B5	BM802200B5	182,41
1,5	2	90S	24	9,6	31	73	2760	0,98	40	0,88	13,5	B3	BM90S2200B3	203,58
												B5	BM90S2200B5	213,73
1,8	2,5	90L	24	12	27,5	84	2820	0,99	55	0,71	16	B3	BM90L2250B3	221,73
												B5	BM90L2250B5	232,83
2,2	3	90L	24	13.6	49,4	71	2810	0,95	60	0,889	16.5	B3	BM90L2300B3	251,60
												B5	BM90L2300B5	264,23

By request, available in B14 form at the same price as the B5 - remember to communicate the code: B14.