

SINGLE-PHASE MOTORS

4-POLE

Insulation class F, 230V



KW	HP	TYPE	Ø SHAFT	I	I.C.C.	η%	R.P.M.	COS. φ	CONDENS. 450V	MP/MN	KG	SHAPE	CODE	€
0,18	0,25	63	11	1,8	4	60	1360	0,92	10	0,8	5	B3	BM634025B3	120,38
												B5	BM634025B5	126,42
0,25	0,33	71	14	2,3	4,6	60	1390	0,98	10	0,89	5,3	B3	BM714033B3	127,63
												B5	BM714033B5	134,04
0,37	0,5	71	14	2,8	9,2	60	1330	0,97	16	0,75	6	B3	BM714050B3	135,32
												B5	BM714050B5	142,11
0,55	0,75	80	19	4,5	13,6	64	1350	0,95	20	0,78	9,5	B3	BM804075B3	160,37
												B5	BM804075B5	165,88
0,75	1	80	19	5,3	16,5	66	1350	0,97	25	0,73	10	B3	BM804100B3	172,88
												B5	BM804100B5	182,41
1,1	1,5	90S	24	7,2	18,7	73	1330	0,99	31,5	0,68	13	B3	BM90S4150B3	218,37
												B5	BM90S4150B5	231,13
1,5	2	90L	24	9,5	24	72	1340	0,99	50	0,7	15	B3	BM90L4200B3	240,41
												B5	BM90L4200B5	249,40
1,8	2,5	90L	24	13,8	33,2	72	1340	0,97	50	0,6	17	B3	BM90L4250B3	274,05
												B5	BM90L4250B5	282,75
2,2	3	100	28	14,8	35,8	71	1340	0,98	60	0,68	20,5	B3	BM1004300B3	304,50
												B5	BM1004300B5	320,45

By request, available in B14 form at the same price as the B5 - remember to communicate the code: B14.

- SHAPE B3 + B5 = +10%
- SHAPE B3 + B14 = +10%