

UNSATURATED DMD FAETISO B2

POLYESTER-DACRON® DACRON® FILM
OBJS2.E317429 DV-155J TAB IX (JOHN c. Dolph's)



OPERATING TEMP.

CLASS	A	105°
CLASS	B	130°
CLASS	F	155°
CLASS	H	180°

THICKNESS mm	BREAKDOWN VOLTAGE kv/mm	THICKNESS FILM μ m	WEIGHT gr/m ² +/- 12%	WIDTH mm	kg	CODE	€/kg
0.15	5.5	50	140	1000	20	0800415-20	25.00
0.20	8.5	100	220	1000	20	0800420-20	24.80
0.22	9.5	125	250	1000	20	0800422-20	24.40
0.29	14	190	345	1000	20	0800429-20	21.70
0.35	17	250	425	1000	20	0800435-20	21.80
0.45	21	350	560	1000	20	0800445-20	22.30

Possibility of providing rolls with H500 with a minimum package of 10 Kg.

Operating temperature:
 - Class B 130 °C in continuous operation
 - Class B/F 130/155°C
 Melting point: 260°C
 Shrinkage at 150 °C: <3%

N.B. The weights of the packs are indicative with a tolerance of +/- 10 %. The widths may be subject to maximum variations of +/- 7,5 %.
 For different cuts, please contact our sales office.
 Tel. 02 89231200 - avvolgimenti@faet.it - Fax 02 89231230