

NOMEX® - POLYESTER FAETISO F2

OBJS2.E317429 DV-155J TAB IX (JOHN c. Dolph's)

OBJS2.E221010 FAET180 IS

OPERATING TEMP.

CLASS	A	105°
CLASS	B	130°
CLASS	F	155°
CLASS	H	180°



THICKNESS mm	BREAKDOWN VOLTAGE kv/mm	THICKNESS FILM μ m	WEIGHT gr/m ² +/- 12%	WIDTH mm	kg	CODE	€/kg
0.19	12	125	220	914	20	0802119-20	36.25
0.25	15	190	317	914	20	0802125-20	29.90
0.31	18	250	390	914	20	0802131-20	26.35
0.36	19	300	466	914	20	0802136-20	27.90
0.41	21	350	550	914	20	0802141-20	27.00

Possibility of providing rolls with H457 with a minimum package of 10 Kg.

Description:

Flexible insulating paper obtained by hot bonding a polyester film and a layer of 50 μ Nomex® insulating paper aramid paper, firmly anchored onto the film by means of special resins, resistant to temperatures in class H.

Nomex® is a registered trademark of Dupont de Nemours
N.B. The weights of the packs are indicative with a tolerance of +/- 10 %
The widths may be subject to maximum variations of +/- 7,5 %
For different cuts, please contact our sales office. Tel. 02 8931200 -
avvolgimenti@faet.it - Fax 02 89231230

MECHANICAL SEALS

PUMPS

EXTRACTOR FANS

MOTORS

INSULATION

EQUIPMENT

MOTOR PARTS

TOOL PARTS

SWITCHES