

NOMEX® T410 DUPONT FAETISO C1


OBJS2.E317429 DV-155J TAB IX (JOHN c. Dolph's)

 QMFZ2.E34739



OPERATING TEMP.

CLASS	A	105°
CLASS	B	130°
CLASS	F	155°
CLASS	H	180°

THICKNESS mm	BREAKDOWN VOLTAGE kv/mm	WEIGHT gr/m ² +/- 12%	WIDTH mm	 kg	CODE	€/kg
0.08	22	64	914	5	0801708-5	185.00
0.13	27	115	914	5	0801713-5	163.50
0.18	33	173	914	5	0801718-5	154.35
0.25	32	248	914	5	0801725-5	151.30
0.30	32	309	914	5	0801730-5	142.30
0.38	33	393	914	5	0801738-5	136.40
0.51	32	546	914	5	0801751-5	143.80
0.76	27	841	914	5	0801776-5	173.30

Possibility of providing rolls with H457 with a minimum package of 5 Kg.

Flammability: Certification V0 UL 94
Insulation: up to 200 °C, Class H

MECHANICAL SEALS

PUMPS

EXTRACTOR FANS

MOTORS

INSULATION

EQUIPMENT

MOTOR PARTS

TOOL PARTS

SWITCHES