


# LEVAPRENE CABLE FAETCAB F2

Class F - Halogen Free



## OPERATING TEMP.

CLASS	A	105°
CLASS	B	130°
<b>CLASS</b>	<b>F</b>	<b>155°</b>
CLASS	H	180°

CROSS SECTION mm <sup>2</sup>	OUTER Ø mm (±0.1)	SHAPE mm <sup>2</sup>	VOLTAGE RATED V.	 m	COLOURS	CODE	€/m
0.35	1.9	11 X 0.2	300/500	300	● ● ○ ● ●	<b>0808102</b>	<b>0.25</b>
0.5	2.1	16 X 0.2	300/500	300	● ● ○ ● ● ● ● *	<b>0808103</b>	<b>0.33</b>
0.75	2.4	24 X 0.2	300/500	300	● ● ○ ● ● ● *	<b>0808104</b>	<b>0.43</b>
1	2.5	32 X 0.2	300/500	300	● ● ○ ● ● ● ● *	<b>0808105</b>	<b>0.51</b>
1.5	2.8	30 X 0.25	450/750	200	● ● ○ ● ● ● *	<b>0808106</b>	<b>0.71</b>
2.5	3.4	50 X 0.25	450/750	200	● ● ○ ● ● ● *	<b>0808108</b>	<b>1.08</b>
4	4.2	56 X 0.30	450/750	100	● ● ○ * ● *	<b>0808110</b>	<b>2.00</b>
6	5.2	48 X 0.40	450/750	100	●	<b>0808111</b>	<b>2.75</b>

\* limited stocks

## DESCRIPTION:

Flexible conductor cord made of annealed tin-coated copper. M3 high-quality rubber insulation.

## OPERATING TEMPERATURE:

Suitable for Class F uses

## ELECTRICAL CHARACTERISTICS:

- Rated voltage (see table)
- Test voltage 2 Kv.

## PHYSICAL CHARACTERISTICS:

- Low fumes and toxic and corrosive gas emission blend.
- Excellent mechanical and oil resistance.

## APPLICATIONS:

Electric motors. Small, medium and large transformers.

N.B.: specify the colour at the time of the order, otherwise whatever is available will be sent. Other colours on request. The price of cables may vary according to the price trends for the raw materials

