

FEP CABLE FAETCAB H1

Certification IMQ - Standard CEI 20-51



OPERATING TEMP.

CLASS	A	105°
CLASS	B	130°
CLASS	F	155°
CLASS	H	180°



1 Flexible concentric core in tin-coated copper

2 FEP fluoroelastomer insulation

CROSS SECTION CONDUCTOR	SHAPE CONDUCTOR	ELECTRIC RESISTANCE MAXIMUM 20°C	THICKNESS OF INSULATION	OUTER Ø RATED	COLOURS	CODE	€/m
0.75	19X0.23	26	0.2	1.55	● ● ○ ●	0808801	0.61
1	19X0.26	19.5	0.2	1.7	● ● ○ ● ●*	0808804	0.77
1.5	19X0.32	13.3	0.25	2.1	● ● ○ ● ●*	0808807	1.18
2.5	19X0.41	7.98	0.25	2.55	● ● ○* ●*	0808809	1.61
4	CLASS 5	4.95	0.35	3.20	● ● ○ ●	0808810**	3.21
6	CLASS 5	3.30	0.35	3.70	● ●	0808811**	4.31

* limited stocks

** non IMQ codes

OPERATING TEMPERATURE: -100°C + 180°C

OPERATING VOLTAGE: 450/750 V
CONDUCTOR: Tin-coated copper

INSULATING MATERIAL: FEP Fluorocarbon Resin in accordance with CEI 20-51
BEND RADIUS: 4X external diameter

MECHANICAL SEALS

PUMPS

EXTRACTOR FANS

MOTORS

INSULATION

EQUIPMENT

MOTOR PARTS

TOOL PARTS

SWITCHES