

# SILICONE RUBBER CABLE

## FAETCAB H2



### OPERATING TEMP.

CLASS	A	105°
CLASS	B	130°
CLASS	F	155°
<b>CLASS</b>	<b>H</b>	<b>180°</b>

CROSS SECTION	COMPOSITION	THICKNESS	EXTERNAL Ø	LINEAR RESISTANCE	COLOURS	CODE	€/m
mm <sup>2</sup>	NUM. X Ø STRANDS mm	WALL mm	RATED mm	MAXIMUM AT 20°C W/KM			
0.5	16X0.2	0.6	2.1	39	○ ● ● ● ● ● ● ● ● *	<b>0808202</b>	<b>0.27</b>
0.75	24X0.2	0.6	2.3	26	○ ● ● ● ● ● ● ● *	<b>0808203</b>	<b>0.36</b>
1	32X0.2	0.6	2.45	19.5	○ ● ● ● ● ● ● *	<b>0808204</b>	<b>0.42</b>
1.5	30X0.25	0.6	2.75	13.3	○ ● ● ● ● ● ● ● ● ● *	<b>0808205</b>	<b>0.60</b>
2.5	50X0.25	0.7	3.45	7.98	○ ● ● ● ● ● ● *	<b>0808206</b>	<b>0.91</b>
4	54X0.3	0.8	4.1	4.95	○ ● ● ● ● ● ● ● *	<b>0808208</b>	<b>1.49</b>
6	80X0.3	0.8	4.7	3.3	○ ● ● ● ● ● ● ● *	<b>0808210</b>	<b>2.17</b>
10	74X0.4	1	6.1	1.91	○ ● ● ● ● ● *	<b>0808211</b>	<b>3.61</b>
16	115X0.4	1.2	7.5	1.21	○ ● ● ● ● ● *	<b>0808212</b>	<b>5.59</b>
25	179X0.4	1.4	9.1	0.78	○ ● ● ● ● ● *	<b>0808213</b>	<b>8.80</b>
35	251X0.4	1.4	10.3	0.554	○ ● ● ● ● ● *	<b>0808214</b>	<b>13.49</b>
50	364X0.4	1.6	12	0.386	○ ● ● ● ● ● *	<b>0808215</b>	<b>18.78</b>
70	336X0.5	1.6	13.7	0.272	○ ● ● ● ● ● *	<b>0808216</b>	<b>25.55</b>
95	432X0.5	1.8	15.6	0.206	○ ● ● ● ● ● *	<b>0808217</b>	<b>32.59</b>
120	576X0.5	1.8	17.4	0.161	○ ● ● ● ● ● *	<b>0808218</b>	<b>44.80</b>

\* limited stocks

OPERATING TEMPERATURE: -60°C + 180°C

BEND RADIUS: 4X external diameter  
AVAILABLE COLOURS: white, red blue, black

OPERATING VOLTAGE:  
300/500 V UP TO 6 MM2 - 0.6/1 KV UPPER CROSS SEC. 6 mm<sup>2</sup>  
CONDUCTOR: Red Copper  
INSULATING MATERIAL: Silicone Rubber