

POLYURETHANE SLEEVE

FAETUBE FP3

Class F - 3 Kv

OBJS2.E317429 DV-155J TAB IX (JOHN c. Dolph's)

OBJS2.E221010 FAET180 IS



OPERATING TEMP.

CLASS	A	105°
CLASS	B	130°
CLASS	F	155°
CLASS	H	180°



INNER Ø RATED mm	 m	CODE	€/m
0.5	200	0806305	0.20
0.8	200	0806308	0.20
1	200	0806310	0.20
1.5	200	0806315	0.23
2	200	0806320	0.25
2.5	200	0806325	0.26
3	200	0806330	0.32
3.5	200	0806335	0.41
4	200	0806340	0.49
4.5	100	0806345	0.58
5	100	0806350	0.62
6	100	0806360	0.72
7	100	0806370	0.91
8	100	0806380	1.04
9	100	0806390	1.32
10	100	0806400	1.47
12	100	0806420	1.77
14	100	0806440	2.11
16	100	0806460	3.00
18	50	0806480	3.74
20	50	0806500	4.41
22	30	0806520	5.07

DESCRIPTION:

Sleeve made from a glass fibre braided sleeve coated with polyurethane varnish.

OPERATING TEMPERATURE: Class F -30°C / +155°C in continuous operation. Withstands peaks of 250 °C

ELECTRICAL CHARACTERISTICS:

Average breakdown voltage: 3Kv.

CHEMICAL CHARACTERISTICS:

Good compatibility with impregnation varnishes.

PHYSICAL CHARACTERISTICS:

- Good adhesion of polyurethane film to the glass fibre sleeve.
 - Impregnating the glass fibre sleeve prevents it from fraying during cutting.
 - Flexible sleeve resistant to bending.
 - Good resistance to ageing and to vibrations.
 - Does not propagate flames.
 - Good resistance to humidity.
- STANDARD COLOURS: hazelnut brown.
On request, greater diameters are available (up to Ø 30 mm)

MECHANICAL SEALS

PUMPS

EXTRACTOR FANS

MOTORS

INSULATION

EQUIPMENT

MOTOR PARTS

TOOL PARTS

SWITCHES