

ACRYLIC SLEEVE

FAETUBE FA3

Class F – 2.5 Kv

OBJS2.E317429 DV-155J TAB IX (JOHN c. Dolph's)

OBJS2.E221010 FAET180 IS



OPERATING TEMP.

CLASS A 105°

CLASS B 130°

CLASS F 155°

CLASS H 180°



INNER Ø RATED mm	 m	CODE	€/m
0.5	200	0805605-STD	0.15
0.8	200	0805608-STD	0.15
1	200	0805610-STD	0.15
1.5	200	0805615-STD	0.17
2	200	0805620-STD	0.21
2.5	200	0805625-STD	0.23
3	200	0805630-STD	0.28
3.5	200	0805635-STD	0.35
4	200	0805640-STD	0.43
5	100	0805650-STD	0.51
6	100	0805660-STD	0.61
7	100	0805670-STD	0.72
8	100	0805680-STD	0.85
9	100	0805690-STD	1.12
10	100	0805700-STD	1.16
12	100	0805720-STD	1.53
14	100	0805740-STD	1.92
16	100	0805760-STD	2.86
18	50	0805780-STD	4.24

DESCRIPTION:

Sleeve made of a type E glass fibre braided sleeve coated with a class F solvent-free acrylic emulsion.

OPERATING TEMPERATURE: Class F -30°C / +155°C in continuous operation

ELECTRICAL CHARACTERISTICS: Average breakdown voltage 3 Kv Max

CHEMICAL CHARACTERISTICS: Good compatibility with impregnation varnishes

PHYSICAL CHARACTERISTICS:

- Impregnating the glass fibre sleeve prevents it from fraying during cutting.

- Low resistance to perforation

- Good resistance

STANDARD COLOURS: yellow

COLOURS ON REQUEST: White, Blue, Black, Red, Green

On request, greater diameters are available (up to Ø 24 mm)

N.B. The codes shown relate to the standard colour: Yellow. To order other colours, replace std with the colour.