

HES SLEEVE FAETUBE HES15

Class H – 1.5 Kv

OBJS2.E317429 DV-155J TAB IX (JOHN c. Dolph's)

OBJS2.E221010 FAET180 IS



OPERATING TEMP.

CLASS	A	105°
CLASS	B	130°
CLASS	F	155°
CLASS	H	180°



INNER Ø RATED mm	 m	CODE	€/m
0.5	200	0806805F-STD	0.13
0.8	200	0806808F-STD	0.13
1	200	0806810F-STD	0.13
1.5	200	0806815F-STD	0.15
2	200	0806820F-STD	0.16
2.5	200	0806825F-STD	0.21
3	200	0806830F-STD	0.24
3.5	200	0806835F-STD	0.28
4	200	0806840F-STD	0.37
5	100	0806850F-STD	0.41
6	100	0806860F-STD	0.48
7	100	0806870F-STD	0.56
8	100	0806880F-STD	0.63
9	100	0806890F-STD	0.74
10	100	0806900F-STD	0.88
12	100	0806920F-STD	1.11
14	100	0806940F-STD	1.36
16	100	0806960F-STD	1.71
18	50	0806980F-STD	2.55
20	50	0807000F-STD	3.33

DESCRIPTION:

Sleeve made of a type E glass fibre braided sleeve coated with a silicone elastomer.

OPERATING TEMPERATURE: Class H -55°C / +250°C in continuous operation. Can withstand peaks up to 290 °C.

ELECTRICAL CHARACTERISTICS:

Standard insulation voltage: 1.5 Kv.

CHEMICAL CHARACTERISTICS: Good resistance to most chemical agents.

STANDARD COLOURS: Brick Red (other colours on request)

PHYSICAL CHARACTERISTICS:

- Excellent flexibility.
- Good resistance.
- Good resistance to vibrations.
- Poor mechanical resistance in the silicone elastomer.
- Good adhesion of the silicone elastomer to the glass fibre sleeve.
- Does not propagate flames.
- Good resistance to humidity.
- UL 1441 fire proof.

On request, greater diameters are available (up to Ø 30 mm)

MECHANICAL SEALS

PUMPS

EXTRACTOR FANS

MOTORS

INSULATION

EQUIPMENT

MOTOR PARTS

TOOL PARTS

SWITCHES