


HES SLEEVE FAETUBE HES25

Class H – 2.5 Kv

OBJS2.E317429 DV-155J TAB IX (JOHN c. Dolph's)

OBJS2.E221010 FAET180 IS



OPERATING TEMP.

CLASS A 105°

CLASS B 130°

CLASS F 155°

CLASS H 180°



INNER Ø RATED mm	 m	CODE	€/m
0.5	200	0806605F-STD	0.16
0.8	200	0806608F-STD	0.16
1	200	0806610F-STD	0.16
1.5	200	0806615F-STD	0.20
2	200	0806620F-STD	0.21
2.5	200	0806625F-STD	0.25
3	200	0806630F-STD	0.30
3.5	200	0806635F-STD	0.38
4	200	0806640F-STD	0.43
5	100	0806650F-STD	0.50
6	100	0806660F-STD	0.58
7	100	0806670F-STD	0.69
8	100	0806680F-STD	0.75
9	100	0806690F-STD	0.94
10	100	0806700F-STD	1.04
12	100	0806720F-STD	1.31
14	100	0806740F-STD	1.72
16	100	0806760F-STD	2.17
18	50	0806780F-STD	3.34
20	50	0806800F-STD	4.63

DESCRIPTION:

Sleeve made of a type E glass fibre braided sleeve coated with a silicone elastomer.

OPERATING TEMPERATURE: Class H -55°C / +250°C in continuous operation. Can withstand peaks up to 290 °C.

ELECTRICAL CHARACTERISTICS:

Standard insulation voltage: 2,5 Kv.

CHEMICAL CHARACTERISTICS:

Good resistance to most chemical agents

PHYSICAL CHARACTERISTICS:

- Excellent flexibility.
- Good resistance.
- Good resistance to vibrations.
- Poor mechanical resistance in the silicone elastomer.
- Good adhesion of the silicone elastomer to the glass fibre sleeve.
- Does not propagate flames.
- Good resistance to humidity.
- UL 1441 fire proof.

STANDARD COLOURS: Brick Red (other colours on request)

On request, greater diameters are available (up to Ø 30 mm)