

## ISOTAPE® 54574 MONO-ADHESIVE TAPE

With GLASS FILAMENTS

**vonRoll**



WIDTH mm	☒ m	CODE	€/pc
19	50	<b>0811019V</b>	<b>6.85</b>
25	50	<b>0811025V</b>	<b>9.00</b>
30	50	<b>0811030V</b>	<b>10.80</b>
38	50	<b>0811038V</b>	<b>13.70</b>
50	50	<b>0811050V</b>	<b>18.00</b>

### CHARACTERISTICS:

- Storage time: 12 months.
- Internal diameter: 76 mm.
- Length: 50 m
- Support: polypropylene film and glass filaments
- Adhesive: synthetic rubber
- Colour: Transparent
- Total thickness: 0.14 mm

- Adhesion to steel: 3.75 N/25 mm.
- Tensile Strength: 125 N/25 mm.
- Elongation: 7%
- Unwinding: 223 g /cm.

N.B.: thanks to the internal cutting department, we are capable of providing any width. Ask our sales office for minimum lots and prices.

Tel. 02 89231200 - avolgimenti@faet.it - Fax 02 89231230

## ISOTAPE® 52402PV3 PAPER TAPE

Reinforced with GLASS

**vonRoll**



### OPERATING TEMP.

CLASS	A	105°
CLASS	B	130°
<b>CLASS</b>	<b>F</b>	<b>155°</b>
CLASS	H	180°

WIDTH mm	☒ m	CODE	€/pc
19	55	<b>0810619V</b>	<b>14.50</b>
25	55	<b>0810625V</b>	<b>19.15</b>
30	55	<b>0810630V</b>	<b>22.90</b>
38	55	<b>0810638V</b>	<b>29.00</b>
50	55	<b>0810650V</b>	<b>38.1</b>

### CHARACTERISTICS:

- Support: Paper + glass filaments
- Support Thickness: 0.2 mm
- Total thickness: 0.26 mm
- Adhesive: acrylic resistant to mineral oils
- Colour: white
- Adhesion to steel: 11.7 N/25 mm
- Tensile Strength: 372 N/25 mm

- Elongation: 18%
- Insulation voltage: 3Kv
- Thermal Class: -20/+155°C
- Specifications: UL510

N.B.: thanks to the internal cutting department, we are capable of providing any width. Ask our sales office for minimum lots and prices.

Tel. 02 89231200 - avolgimenti@faet.it - Fax 02 89231230