

ISOTAPE® 4428PV3 ADHESIVE TAPE

POLYIMIDE

 OANZ2.E315249

OPERATING TEMP.

CLASS	A	105°
CLASS	B	130°
CLASS	F	155°
CLASS	H	180°

CHARACTERISTICS

- Support: polyimide
- Adhesive: thermosetting silicone
- Total thickness: 0.064 mm
- Adhesive resistance: 5.7 N/25mm
- Traction resistance: 122 N/25mm.
- Electric strength: 6,5 Kv.

vonRoll



WIDTH mm	 m	CODE	€/pc
12	33	0809912K	18.85
15	33	0809915K	22.90
19	33	0809919K	29.00
25	33	0809925K	37.40
30	33	0809930K	44.85

- Elongation: 70%
- Dielectric strength: 7 Kv.
- Insulation class: 180°C

N.B.: thanks to the internal cutting department, we are capable of providing any width. Ask our sales office for minimum lots and prices.

Tel. 02 89231200 - avvolgimenti@faet.it - Fax 02 89231230

INTERTAPE 4118 ADHESIVE TAPE

KAPTON®

 OANZ2.E20780

OPERATING TEMP.

CLASS	A	105°
CLASS	B	130°
CLASS	F	155°
CLASS	H	180°

CHARACTERISTICS:

- Support: Kapton®
- Adhesive: thermosetting silicone
- Total thickness: 0.063mm
- Adhesive resistance: 7 N/25mm
- Traction resistance: 130 N/25mm

vonRoll



WIDTH mm	 m	CODE	€/pc
12	33	0809912K-1	24.30
15	33	0809915K-1	30.35
19	33	0809919K-1	38.45
25	33	0809925K-1	50.55
30	33	0809930K-1	60.70

- Elongation: 60 %
- Dielectric strength: 7 Kv
- Insulation class: 180°C

N.B.: thanks to the internal cutting department, we are capable of providing any width. Ask our sales office for minimum lots and prices.

Tel. 02 89231200 - avvolgimenti@faet.it - Fax 02 89231230

MECHANICAL SEALS

PUMPS

EXTRACTOR FANS

MOTORS

INSULATION

EQUIPMENT

MOTOR PARTS

TOOL PARTS

SWITCHES