

INTERTAPE 4429 ADHESIVE TAPE

POLYIMIDE 2mils

 OANZ2.E20780

vonRoll



OPERATING TEMP.

CLASS	A	105°
CLASS	B	130°
CLASS	F	155°
CLASS	H	180°

WIDTH mm	 m	CODE	€/pc
19	33	0809919K-2	74.55
25	33	0809925K-2	98.10
30	33	0809930K-2	117.80

CHARACTERISTICS:

- Support: Polyimide
- Adhesive: thermosetting silicone
- Total thickness: 0,089mm
- Adhesive resistance: 5.5 N/25mm
- Traction resistance: 285 N/25mm
- Elongation: 60 %

- Dielectric strength: 11 Kv
- Insulation class: 180°C

N.B.: thanks to the internal cutting department, we are capable of providing any width. Ask our sales office for minimum lots and prices.

Tel. 02 89231200 - avvolgimenti@faet.it - Fax 02 89231230

NITTO 15 ADHESIVE TAPE

SELF-AMALGAMATING

Nitto



WIDTH mm	 m	CODE	€/pc
19	5	0811920	7.70

CHARACTERISTICS:

- Application temperature: -10° + 40°
- Max operating temperature: 65° continuous - 100° peak
- Thickness: 0.75 mm.
- Tensile Strength: at 23 °C 3.2 N/mm2

- Elongation: at 23 °C 550%
- Breakdown voltage: 44Kv./mm.
- Dielectric constant: 2.6
- Resistance to ozone: good