

P.31 ADHESIVE TAPE

Yellow POLYESTER

 OANZ2.E178430



OPERATING TEMP.

CLASS	A	105°
CLASS	B	130°
CLASS	F	155°
CLASS	H	180°

WIDTH mm	 m	CODE	€/pc
12	66	H0-P31-12	3.15
15	66	H0-P31-15	3.95
19	66	H0-P31-19	5.00
25	66	H0-P31-25	6.25
30	66	H0-P31-30	7.90

CHARACTERISTICS:

- Total Thickness: 0.060 mm
- Adhesion to Steel: 4.5 N/cm
- Elongation: 90%
- Tensile Strength: 40 N/cm
- Breakdown Voltage: 4.5 Kv

Available in BLUE colour on request.

N.B.: thanks to the internal cutting department, we are capable of providing any width. Ask our sales office for minimum lots and prices.

Tel. 02 89231200 - avvolgimenti@faet.it - Fax 02 89231230

PR.25 ADHESIVE TAPE

Polyester with glass FILAMENTS

 OANZ2.E178430



OPERATING TEMP.

CLASS	A	105°
CLASS	B	130°
CLASS	F	155°
CLASS	H	180°

WIDTH mm	 m	CODE	€/pc
19	50	H0-PR25-19	6.65
25	50	H0-PR25-25	8.75
30	50	H0-PR25-30	10.50
38	50	H0-PR25-38	13.30
50	50	H0-PR25-50	17.50

CHARACTERISTICS:

- Total Thickness: 0.13 mm
- Adhesion to Steel: 3.2 N/cm
- Elongation: 5%
- Tensile Strength: 200 N/cm

- Breakdown Voltage: 5 Kv

N.B.: thanks to the internal cutting department, we are capable of providing any width. Ask our sales office for minimum lots and prices.

Tel. 02 89231200 - avvolgimenti@faet.it - Fax 02 89231230

MECHANICAL SEALS

PUMPS

EXTRACTOR FANS

MOTORS

INSULATION

EQUIPMENT

MOTOR PARTS

TOOL PARTS

SWITCHES