

RB 9


GRAPHITE/ALUMINA/NBR

BVP

Rotation: bi directional
 Stationary ring: with cup
 Max pressure: 10 bar
 Temperature: -25° max +90°

Use: water, clean liquids

LIQUIBLOK



Dimensions mm

SHAFT	ROTATING PART		STATIONARY RING		COMPLETE MECHANICAL SEAL	
d1	d3	L	d7	I4	CODE	€
10	23.5	18	24	7	0309010	4.19
11	23.5	18	24	7	0309011	4.92
12	26	18	26	7	0309012	6.05
14	28	18.5	28	7	0309014	6.59
15	30	22.5	28	7	0309015	7.77
16	32	23.5	32	10	0309016	8.38
18	32.5	26.5	35	10	0309018	9.57
19	32.5	26.5	35	10	0309019	10.77
20	35.5	28	38	10	0309020	11.38
22	37.5	30.3	40	10	0309022	15.56
25	42	29.3	44	10	0309025	17.94
28	45.5	30	46	10	0309028	25.12
30	48	30	50	10	0309030	28.70
32	50	30	54	10	0309032	32.28
35	54.5	32	58	10	0309035	37.68
38	58.5	32.6	60	10	0309038	40.66
40	62.5	32.6	64	10	0309040	44.25
45	66.5	35	66	10	0309045	50.82
50	72.5	44.6	72	10	0309050	65.17
55	76	47	78	12	0309055	71.15

RB 15


GRAPHITE/ALUMINA/NBR

BVP

Rotation: bi directional
 Stationary ring: with cup
 Max pressure: 4 bar
 Temperature: -25° max +90°

Use: water, clean liquids

LIQUIBLOK



Dimensions mm

SHAFT	ROTATING PART		STATIONARY RING		COMPLETE MECHANICAL SEAL	
d1	d3	L	d7	I4	CODE	€
15	31.5	24	29.5	8	0315015	5.00
16	31.5	24	29.5	8	0315016	5.21