

## PT.25 ADHESIVE TAPE


tnt POLYESTER

 OANZ2.E178430



### OPERATING TEMP.

CLASS	A	105°
<b>CLASS</b>	<b>B</b>	<b>130°</b>
CLASS	F	155°
CLASS	H	180°

WIDTH mm	 m	CODE	€/pc
19	50	<b>HO-PT25-19</b>	<b>5.50</b>
25	50	<b>HO-PT25-25</b>	<b>7.25</b>
30	50	<b>HO-PT25-30</b>	<b>8.70</b>
38	50	<b>HO-PT25-38</b>	<b>11.00</b>
50	50	<b>HO-PT25-50</b>	<b>14.50</b>

### CHARACTERISTICS:

- Total Thickness: 0.14 mm
- Adhesion to Steel: 5 N/cm
- Elongation: 15%
- Tensile Strength: 25 N/cm

- Breakdown Voltage: 4.8 Kv

N.B.: thanks to the internal cutting department, we are capable of providing any width. Ask our sales office for minimum lots and prices.

Tel. 02 89231200 - avolgimenti@faet.it - Fax 02 89231230

## PX.50 ADHESIVE TAPE


NOMEX® Polyester

 OANZ2.E178430



### OPERATING TEMP.

CLASS	A	105°
CLASS	B	130°
<b>CLASS</b>	<b>F</b>	<b>155°</b>
CLASS	H	180°

WIDTH mm	 m	CODE	€/pc
19	50	<b>HO-PX50-19</b>	<b>17.60</b>
25	50	<b>HO-PX50-25</b>	<b>23.15</b>
30	50	<b>HO-PX50-30</b>	<b>27.80</b>
38	50	<b>HO-PX50-38</b>	<b>35.15</b>
50	50	<b>HO-PX50-50</b>	<b>46.30</b>

### CHARACTERISTICS:

- Total Thickness: 0.13 mm
- Adhesion to Steel: 5.5 N/cm
- Elongation: 10%
- Tensile Strength: 65 N/cm

Breakdown Voltage: 7 Kv

N.B.: thanks to the internal cutting department, we are capable of providing any width. Ask our sales office for minimum lots and prices.

Tel. 02 89231200 - avolgimenti@faet.it - Fax 02 89231230