

# COPPER WIRE, PVC INSULATED

*For submersible pumps*

| DESCRIPTION           | VOLTAGE | M.U. | BUNDLES mt | kg     | BUNDLE Kg | CODE           |
|-----------------------|---------|------|------------|--------|-----------|----------------|
| mm 1.4-2.2* MM2 1.54  | V 600   | M    | 600        | 16.88  | 10.13     | <b>PVC1422</b> |
| mm 1.5-2.1 MM2 1.77   | V 380   | M    | 600        | 18.11  | 10.87     | <b>PVC1521</b> |
| mm 1.5-2.2* MM2 1.77  | V 380   | M    | 600        | 18.58  | 11.15     | <b>PVC1522</b> |
| mm 1.5-2.3* MM2 1.77  | V 600   | M    | 500        | 19.08  | 9.54      | <b>PVC1523</b> |
| mm 1.6-2.3* MM2 2.01  | V 380   | M    | 500        | 20.90  | 10.45     | <b>PVC1623</b> |
| mm 1.6-2.4* MM2 2.01  | V 600   | M    | 500        | 21.42  | 10.71     | <b>PVC1624</b> |
| mm 1.7-2.4* MM2 2.27  | V 380   | M    | 500        | 23.37  | 11.68     | <b>PVC1724</b> |
| mm 1.7-2.5* MM2 2.27  | V 600   | M    | 400        | 23.90  | 9.56      | <b>PVC1725</b> |
| mm 1.8-2.5* MM2 2.54  | V 380   | M    | 400        | 25.97  | 10.39     | <b>PVC1825</b> |
| mm 1.8-2.6* MM2 2.54  | V 600   | M    | 400        | 26.53  | 10.61     | <b>PVC1826</b> |
| mm 1.8-2.7 MM2 2.54   | V 600   | M    | 900        | 27.11  | 24.40     | <b>PVC1827</b> |
| mm 1.9-2.6* MM2 2.84  | V 600   | M    | 400        | 28.71  | 11.48     | <b>PVC1926</b> |
| mm 1.9-2.7* MM2 2.84  | V 600   | M    | 900        | 29.29  | 26.36     | <b>PVC1927</b> |
| mm 1.9-2.8 MM2 2.84   | V 600   | M    | 900        | 29.89  | 26.90     | <b>PVC1928</b> |
| mm 1.9-2.9* MM2 2.84  | V 600   | M    | 800        | 30.52  | 24.42     | <b>PVC1929</b> |
| mm 2.0-2.8 MM2 3.14   | V 380   | M    | 900        | 32.19  | 28.97     | <b>PVC2028</b> |
| mm 2.0-2.9* MM2 3.14  | V 600   | M    | 800        | 32.82  | 26.25     | <b>PVC2029</b> |
| mm 2.0-3.0* MM2 3.14  | V 600   | M    | 600        | 33.47  | 26.77     | <b>PVC2030</b> |
| mm 2.1-3.0* MM2 3.46  | V 600   | M    | 600        | 35.88  | 28.70     | <b>PVC2130</b> |
| mm 2.2-3.1* MM2 3.80  | V 600   | M    | 500        | 39.08  | 27.36     | <b>PVC2231</b> |
| mm 2.3-3.2* MM2 4.15  | V 380   | M    | 500        | 42.43  | 25.46     | <b>PVC2332</b> |
| mm 2.3-3.3 MM2 4.15   | V 600   | M    | 500        | 43.14  | 25.89     | <b>PVC2333</b> |
| mm 2.4-3.3 MM2 4.52   | V 380   | M    | 400        | 45.91  | 27.55     | <b>PVC2433</b> |
| mm 2.4-3.4* MM2 4.52  | V 600   | M    | 400        | 46.65  | 27.99     | <b>PVC2434</b> |
| mm 2.4-3.5 MM2 4.52   | V 600   | M    | 400        | 47.41  | 28.44     | <b>PVC2435</b> |
| mm 2.5-3.5* MM2 4.90  | V 600   | M    | 400        | 50.29  | 30.18     | <b>PVC2535</b> |
| mm 2.7-3.9* MM2 5.73  | V 600   | M    | 300        | 59.67  | 23.87     | <b>PVC2739</b> |
| mm 2.8-4.0* MM2 6.15  | V 600   | M    | 300        | 63.78  | 25.51     | <b>PVC2840</b> |
| mm 2.9-4.1* MM2 6.61  | V 600   | M    | 300        | 68.03  | 27.21     | <b>PVC2941</b> |
| mm 3.0-4.2* MM2 7.07  | V 600   | M    | 300        | 72.42  | 28.97     | <b>PVC3042</b> |
| mm 3.2-4.4 MM2 8.04   | V 600   | M    | 300        | 81.61  | 24.48     | <b>PVC3244</b> |
| mm 3.2-4.7* MM2 8.04  | V 600   | M    | 300        | 84.61  | 21.15     | <b>PVC3247</b> |
| mm 3.4-4.6* MM2 9.07  | V 380   | M    | 300        | 91.37  | 22.84     | <b>PVC3446</b> |
| mm 3.5-5.1* MM2 9.62  | V 600   | M    | 250        | 100.76 | 25.19     | <b>PVC3551</b> |
| mm 3.6-5.2* MM2 10.18 | V 600   | M    | 250        | 106.07 | 26.52     | <b>PVC3652</b> |
| mm 3.7-5.1* MM2 10.75 | V 380   | M    | 250        | 109.24 | 27.31     | <b>PVC3751</b> |
| mm 3.8-5.4* MM211.34  | V 600   | M    | 200        | 117.12 | 23.42     | <b>PVC3854</b> |
| mm 4.0-5.6* MM212.56  | V 600   | M    | 200        | 128.73 | 25.75     | <b>PVC4056</b> |

\* The information contained in this bulletin is the result of accurate research and numerous laboratory experiments.  
However, considering the many practical applications, they are provided as an example only, and we decline any responsibility.

For prices and packs, please contact our sales office.  
Tel. 02 89231200 - [avvolgimenti@faet.it](mailto:avvolgimenti@faet.it)