

# HAMMER SOLDERING IRONS

180W



| MODELL X A | W       |     | CODE              | €/pc          |
|------------|---------|-----|-------------------|---------------|
| 1822A/2    | 260X145 | 180 | <b>B018220018</b> | <b>170.10</b> |

Measurements in mm

# TIN WIRE AND BARS

*For welding*



TIN-COPPER **ALLOY** 99.3/0.7  
SUITABLE FOR WELDING ELECTRICAL WIRES.

| TIN CONTENT | COPPER<br>CONTENT | MELTING<br>POINT | SPECIFIC<br>WEIGHT | OPERATING<br>TEMPERATURE | Ø OF TIN<br>WIRE | g    | CODE           | €/kg              |
|-------------|-------------------|------------------|--------------------|--------------------------|------------------|------|----------------|-------------------|
| 99.3 ± 0.2% | 0.7 ± 0.2%        | 227°C            | 7.3                | 300°C to 450°C           | 1.5              | 1000 | <b>3003216</b> | <b>On request</b> |
|             |                   |                  |                    |                          | 2                | 1000 | <b>3003221</b> |                   |

| BAR MEASUREMENTS<br>IN MM | g    | CODE           | €/kg              |
|---------------------------|------|----------------|-------------------|
| 4 x 7 x 400               | 1000 | <b>3003240</b> | <b>On request</b> |

TIN-SILVER **ALLOY** 96/4

| TIN CONTENT | COPPER<br>CONTENT | MELTING<br>POINT | SPECIFIC<br>WEIGHT | OPERATING<br>TEMPERATURE | Ø OF TIN<br>WIRE | g    | CODE           | €/kg              |
|-------------|-------------------|------------------|--------------------|--------------------------|------------------|------|----------------|-------------------|
| 96.5 ± 0.2% | 3.5 ± 0.2%        | 221°C            | 7.3                | 350°C to 460°C           | 1.5              | 1000 | <b>3003217</b> | <b>On request</b> |
|             |                   |                  |                    |                          | 2                | 1000 | <b>3003218</b> |                   |