


CAPACITORS

CAPACITORS

450 VOLT



CAPACITY μF	$\varnothing$	HEIGHT	pcs	CODE	€/pc
2	28	55	6	0601001	2,20
2.5	28	55	6	0601002	2,24
3.15	28	55	6	0601003	2,30
4	28	55	6	0601004	2,33
5	28	55	6	0601005	2,54
6.3	32	55	6	0601006	2,59
8	32	55	6	0601007	2,83
10	36	58	6	0601008	2,94
12.5	36	70	6	0601009	3,41
14	36	70	6	0601010	3,59
16	36	70	6	0601011	4,10
18	40	70	6	0601012	4,83
20	40	70	6	0601013	5,01
25	40	92	6	0601014	5,61
30	40	92	6	0601015	6,40
32	45	92	6	0601016	6,58
35	45	92	3	0601017	7,24
40	45	92	3	0601018	8,33
45	50	92	3	0601019	8,89
50	50	92	3	0601020	9,54
55	50	92	3	0601021	10,24
60	50	117	3	0601022	11,56
70	50	117	3	0601023	12,08
80	55	120	3	0601024	14,35

dimensions in mm

HOOD	
CODE	€/pc
0601070	0.53

For spares see page 443.

The principal features of this series of capacitors are:

- Low leakage anti-inductive winding
- Self-regenerating properties that prevent short-circuiting
- Small size and light weight
- The capacitor is completely free of risks of liquid leaks.
- Safety class: PO

Type approvals: EN 60252-1 VDE IMQ ASE CE

TECHNICAL FEATURES:

Power supply 450 Volt 50 Hz

Lifespan 3000 hours

Capacity tolerance: $\pm 5\%$

Working frequency: from 50 to 60 Hz

Protection level: IP00

Plastic housing with double 6,3 mm Faston fixings