


ELECTRIC CAPACITORS

450 VOLT
with threaded tang



CAPACITY μF	$\varnothing$	HEIGHT	pcs	CODE	€/pc
1.5	28	55	6	0601029	2,26
2	28	55	6	0601030	2,33
2.5	28	55	6	0601031	2,40
3.15	28	55	6	0601032	2,43
4	28	55	6	0601033	2,46
5	28	55	6	0601034	2,71
6.3	32	55	6	0601035	2,75
8	32	55	6	0601036	2,97
10	36	58	6	0601037	3,06
12.5	36	70	6	0601038	3,57
14	36	70	6	0601039	3,72
16	36	70	6	0601040	4,23
18	40	70	6	0601041	4,96
20	40	70	6	0601042	5,12
25	40	92	6	0601043	5,76
30	40	92	6	0601044	6,52
32	45	92	6	0601045	6,73
35	45	92	3	0601046	7,37
40	45	92	3	0601047	8,45
45	50	92	3	0601048	9,03
50	50	92	3	0601049	9,64
55	50	92	3	0601050	10,34
60	50	117	3	0601051	11,69
70	50	117	3	0601052	12,18
80	55	120	3	0601053	14,48

dimensions in mm

HOOD

CODE	€/pc
0601070	0.53

For spares see page 443.

The principal features of this series of capacitors are:

- Low leakage anti-inductive winding
- Self-regenerating properties that prevent short-circuiting
- Small size and light weight
- The capacitor is completely free of risks of liquid leaks.
- Safety class: P0

Type approvals: EN 60252-1 VDE IMQ ASE CE

TECHNICAL FEATURES:

- Power supply 450 Volt 50 Hz
- Lifespan 3000 hours
- Capacity tolerance: $\pm 5\%$
- Working frequency: from 50 to 60 Hz
- Protection level: IP00
- Plastic housing with double 6,3 mm Faston fixings:
 - $\varnothing 28$ and 32 M8 plastic tang
 - $\varnothing 25, 30, 36$ to 60 M8 plastic tang

MECHANICAL SEALS

PUMPS

FANS

MOTORS

INSULATION

EQUIPMENT

MOTOR SPARES

TOOL SPARES

SWITCHES