

ELECTRIC CAPACITORS


DUCATI energia s.p.a.

450 VOLT
With 250 mm two-pole cable


CAPACITY μ F	Ø	HEIGHT	pcs	CODE	€/pc
7	32	55	6	0601080	3,44
8	32	55	6	0601081	3,59
10	36	58	6	0601082	3,70
12.5	36	70	6	0601083	4,20
14	36	70	6	0601084	4,40
16	36	70	6	0601085	4,86
18	40	70	6	0601086	5,59
20	40	70	6	0601087	5,76
25	40	92	6	0601088	6,43
30	40	92	6	0601089	7,19
32	45	92	6	0601090	7,37
35	45	92	3	0601091	8,00
40	45	92	3	0601092	9,08
45	50	92	3	0601093	9,64
50	50	92	3	0601094	10,29
55	50	92	3	0601095	10,99
60	50	117	3	0601096	12,32
65	50	117	3	0601097	12,50
70	50	117	3	0601098	12,83
75	50	117	3	0601099	13,91
80	55	120	3	0601100	15,10
90	55	120	1	0601101	17,27
100	60	120	1	0601102	19,03

dimensions in mm

The principal features of this series of capacitors are:

- Low leakage anti-inductive winding
- Self-regenerating properties that prevent short-circuiting
- Small size and light weight
- The capacitor is completely free of risks of liquid leaks.
- Safety class: PO

Type approvals: EN 60252-1 VDE IMQ ASE CE

TECHNICAL FEATURES:

Power supply 450 Volt 50 Hz

Lifespan 3000 hours

 Capacity tolerance: $\pm 5\%$

Working frequency: from 50 to 60 Hz

Protection level: IP55

Plastic housing with 250 mm long two-pole cable