


TRAPEZOIDAL BELTS

SPA

Narrow section DIN 7753 - ISO 4184



Type	Lw	La*	CODE	€/pc
SPA	800	818	3304805	9,00
SPA	807	825	3304806	9,09
SPA	832	850	3304807	9,31
SPA	850	868	3304808	9,54
SPA	857	875	3304809	9,65
SPA	882	900	3304810	9,92
SPA	900	918	3304811	10,12
SPA	907	925	3304812	10,14
SPA	925	943	3304813	10,34
SPA	932	950	3304814	10,42
SPA	950	968	3304815	10,71
SPA	957	975	3304816	10,74
SPA	982	1000	3304817	11,06
SPA	1000	1018	3304818	11,25
SPA	1007	1025	3304819	11,30
SPA	1032	1050	3304820	11,56
SPA	1060	1078	3304821	11,94
SPA	1082	1100	3304822	12,13
SPA	1107	1125	3304823	12,43
SPA	1120	1138	3304824	12,59
SPA	1132	1150	3304825	12,71
SPA	1157	1175	3304826	13,00
SPA	1180	1198	3304827	13,25

Type	Lw	La*	CODE	€/pc
SPA	1207	1225	3304828	13,56
SPA	1232	1250	3304829	13,85
SPA	1250	1268	3304830	14,01
SPA	1257	1275	3304831	14,13
SPA	1272	1290	3304832	14,29
SPA	1282	1300	3304833	14,36
SPA	1307	1325	3304834	14,70
SPA	1320	1338	3304835	14,81
SPA	1332	1350	3304836	14,96
SPA	1357	1375	3304837	15,25
SPA	1382	1400	3304838	15,50
SPA	1400	1418	3304839	15,69
SPA	1407	1425	3304840	15,81
SPA	1425	1443	3304841	16,04
SPA	1432	1450	3304842	16,10
SPA	1457	1475	3304843	16,33
SPA	1482	1500	3304844	16,67
SPA	1500	1518	3304845	16,87
SPA	1507	1525	3304846	16,92
SPA	1532	1550	3304847	17,18
SPA	1557	1575	3304848	17,43
SPA	1582	1600	3304849	17,77
SPA	1600	1618	3304850	17,97

*External length in mm

TECHNICAL FEATURES:

Base by height – b x h:	12,7 x 10
Lower width	5,8
Original width	11,0
Nominal/original length	Lw
External length La	Lw + 18

Internal length	Lw - 45
Minimum diameter cons. Dw	90
Working temperature °C	-30/+70
Weight per meter kg/m	0,119

All sections with related dimensions can be supplied by request.