

CABLE GLANDS TEAR PROOF




TEAR PROOF CABLE GLAND - SUPPLIED COMPLETE WITH NUT

AG	$\varnothing$	GL	$\varnothing$	H	CODE	€/pc
PG7	3-6,5	8	15	21	3307941	0,90
PG9	4-8	8	19	22	3307942	0,95
PG11	5-10	8	22	25	3307943	1,08
PG13,5	6-12	9	24	27	3307944	1,36
PG16	10-14	10	27	28	3307945	1,58
PG21	13-18	11	33	31	3307946	2,20
PG29	18-25	11	42	39	3307947	3,74
PG36	22-32	13	53	48	3307948	4,70
PG42	32-38	13	60	49	3307949	5,86

dimensions in mm; Packages: Single items

Nylon 66 UL 94V-2
Protection level IP 68
Working temperature -20°C to +80°C



TEAR PROOF CABLE GLAND - METRIC PITCH COMPLETE WITH NUT


AG	$\varnothing$	GL	$\varnothing$	H	CODE	€/pc
M12x1,5	3-6,5	8	15	21	3307950	0,94
M16x1,5/11	5-10	8	22	22	3307951	1,03
M20x1,5/16	10-14	10	27	27	3307952	1,29
M25x1,5	13-18	11	33	31	3307953	2,09
M32x1,5	18-25	11	42	39	3307954	3,55
M40x1,5	22-32	13	53	48	3307955	4,48
M50x1,5	32-38	13	60	49	3307956	5,57
M63x1,5	37-44	14	68	49	3307957	7,20



CABLE GLANDS TEAR PROOF CURVED



TEAR PROOF CABLE GLAND, 90° BEND COMPLETE WITH NUT, COLOUR BLACK



D1	NPT npt thread	D2	B1	L1	L2	L3	L	H	Cable Range	CODE	€/pc
16,6	NPT 3/8"	12	9,3	11,7	9,85	16,7	48,5	30	5-9	3307958	2,98
21	NPT 3/8"	14	13	14,7	11,75	18,4	51,6	31,2	10-13	3307959	3,71
26,3	NPT 3/8"	19,2	16,4	14,8	12,55	22,3	64,5	41,6	13-16	33079591	5,56
41,7	NPT 3/8"	31,6	29,3	18,8	16,25	31	85	53	22-29	33079592	10,43

Nylon 66 UL 94V-2
Protection level IP 68
Working temperature -40°C to +85°C