

# FORK FOR POWER

10 - 70 mm<sup>2</sup> - Tinned copper tube



Section R mm <sup>2</sup> F	Ø	C	B	L	☒ pcs	CODE	€/pc
10	6	4,6	11	29	100	<b>3307346</b>	<b>0,42</b>
16	6	6	12	30	100	<b>3307356</b>	<b>0,67</b>
25	6	7	13	33	100	<b>3307368</b>	<b>0,67</b>



Particularly suitable for new switches with captive screw connections. Also available with a different screw hole

# TERMINAL PRE-INSULATED QUICK COUPLING

0,25 - 6 mm<sup>2</sup> - Electrolytic copper 99,9 Tinned




MALE



SELF-EXTINGUISHING PVC TUBE

Colour	Section mm <sup>2</sup>	AWG	A	B	C	L	☒ pcs	CODE	€/pc
•	0,25-1,5	22÷16	6,3X0,8	8	1,8	21	100	<b>3307530</b>	<b>0,13</b>
•	1,5-2,5	16÷14	6,3X0,8	8	2,3	21	100	<b>3307532</b>	<b>0,14</b>
•	2,5-6	12÷10	6,3X0,8	8	3,6	25	100	<b>3307534</b>	<b>0,21</b>

ROUND POINT



SELF-EXTINGUISHING PVC TUBE

Colour	Section mm <sup>2</sup>	AWG	A	B	C	L	☒ pcs	CODE	€/pc
•	0,25-1,5	22-16	1,7	9	1,8	20,5	100	<b>3307571</b>	<b>0,10</b>
•	1,5-2,5	16-14	1,8	11	2,3	22	100	<b>3307573</b>	<b>0,11</b>
•	2,5-6	12-10	2,6	13	3,6	27,5	100	<b>3307575</b>	<b>0,19</b>