

RB 70


WIDIA/WIDIA/FKM

UUV

Rotation: bi directional
 Stationary ring: with O-ring
 Max pressure: 6 bar
 Temperature: -30° max +180°
 for water max +120°

Use: acids, hydrocarbons in the presence of abrasives

LIQUIBLOK



ROTATING PART

Dimensions mm			CODE	€
d1	d3	L		
12	24	13	0207005	34.78
14	32	13	0207011	36.34
15	32	13	0207015	36.34
16	32	13	0207019	36.34
17	39	13	0207023	39.36
18	39	13	0207025	39.36
19	39	13	0207027	39.36
20	39	13	0207029	39.36
20	42	13	0207031	46.95
22	42	13	0207033	46.95
24	47	14	0207037	58.83
25	47	14	0207039	58.83
28	54	15	0207041	71.12
30	54	15	0207043	71.12
32	54	15	0207045	71.12
35	60	16	0207047	89.98
38	65	17	0207049	106.42
40	65	17	0207051	106.42
45	70	20	0207053	113.17
50	85	20	0207055	154.00
60	105	30	0207057	235.03
65	105	30	0207059	279.30
70	115	32	0207061	287.25

STATIONARY RING

Dimensions mm			CODE	€
Hole Ø	d7	I4		
13	26	8	0257003	24.66
16	35	8	0257005	29.55
16	35	8	0257005	29.55
18	38	8	0257009	31.11
21	42	8	0257011	34.34
21	42	8	0257011	34.34
21	42	8	0257011	34.34
21	42	8	0257011	34.34
26	45	10	0257013	42.97
26	45	10	0257013	42.97
27	50	10	0257015	51.68
27	50	10	0257015	51.68
34	57	10	0257017	64.30
34	57	10	0257017	64.30
34	57	10	0257017	64.30
37	63	10	0257019	77.72
42	68	12	0257021	93.27
42	68	12	0257021	93.27
47	73	12	0257023	133.69
52	88	15	0257025	126.75
63	110	15	0257027	192.76
67	110	15	0257057	323.00
72	110	15	0257029	255.55

MECHANICAL SEALS

PUMPS

EXTRACTOR FANS

MOTORS

INSULATION

EQUIPMENT

MOTOR PARTS

TOOL PARTS

SWITCHES