

# MULTI-POLE CABLES



*Flexible for tools and submersible pumps*

## H05RR-F

N° CONDUCTORS	RATED CROSS SECTION MM <sup>2</sup>	Ø EXTERNAL		Ø CONDUCTOR STRANDS	CODE	€/m
		MIN	MAX			
2	0.75	6.0	8.2	0.21	<b>3316275</b>	<b>0.85</b>

For electric tools, rubber insulation with rubber sub-sheath.

Rated voltage 300/500 V.

## H07RN-F

N° CONDUCTORS	RATED CROSS SECTION MM <sup>2</sup>	Ø EXTERNAL		Ø CONDUCTOR STRANDS	CODE	€/m
		MIN	MAX			
2	1	8.0	10.5	0.21	<b>3317210</b>	<b>1.25</b>
	1.5	9.0	11.5	0.26	<b>3317215</b>	<b>1.64</b>
3G	1	8.6	11.5	0.21	<b>3317310</b>	<b>1.61</b>
	1.5	9.6	12.5	0.26	<b>3317315</b>	<b>2.15</b>
	2.5	11.5	14.5	0.26	<b>3317325</b>	<b>3.25</b>
	4	13.0	16.0	0.31	<b>3317340</b>	<b>4.69</b>
4G	1	9.6	12.5	0.21	<b>3317410</b>	<b>2.45</b>
	1.5	10.5	13.5	0.26	<b>3317415</b>	<b>2.64</b>
	2.5	12.5	15.5	0.26	<b>3317425</b>	<b>4.25</b>

G: ground wire present

For electric tools and submersible pumps, rubber insulation with heavy polychloroprene sub-sheath.  
Rated voltage 450/750 V.

Packs: 100 m reels.  
N.B: The price of cables may vary according to the price trends for the raw materials