


# CIRCUIT BREAKERS SERIES DS


## Rear-mount switches




FINISHES IP66, FIXING WITH SCREWS

	MODEL FLANGE	POLES	CURRENT RATED	CODE	€/pc
 <p>FASTENS with 2 screws</p>	<b>RK6</b> FORMAT Grey flange 67x67 mm Lockable, black handle	3	20A	<b>DS0203RRK6</b>	<b>26.90</b>
		3	32A	<b>DS0323RRK6</b>	<b>28.90</b>
		3	40A	<b>DS0403RRK6</b>	<b>34.54</b>
	<b>RL6</b> FORMAT Yellow flange 67x67 mm Lockable, red handle	3	20A	<b>DS0203RRL6</b>	<b>26.90</b>
		3	32A	<b>DS0323RRL6</b>	<b>28.90</b>
		3	40A	<b>DS0403RRL6</b>	<b>34.54</b>
	<b>Y4L</b> FORMAT Yellow flange 48x48 mm Lockable red handle	3	20A	<b>DS0203RQY4L</b>	<b>26.02</b>
		3	32A	<b>DS0323RQY4L</b>	<b>28.08</b>
		3	40A	<b>DS0403RQY4L</b>	<b>33.72</b>

FINISH IP66, SINGLE HOLE AND NUT FIXING

	MODEL FLANGE	POLES	CURRENT RATED	CODE	€/pc
 <p>FASTENS Ø 22 mm hole</p>	<b>GDL6</b> FORMAT Yellow flange 67x67 mm Lockable, red handle	3	20A	<b>DS0203GDL6</b>	<b>32.18</b>
		3	32A	<b>DS0323GDL6</b>	<b>33.87</b>
		3	40A	<b>DS0403GDL6</b>	<b>39.53</b>

ADDITIONAL POLES

PHOTO	DESCRIPTION	CODE	€/pc
	4 <sup>TH</sup> POLE EARLY CLOSING (FOR NEUTRAL) ON BACK OF PANEL	<b>DSC040PAR</b>	<b>11.53</b>
	4 <sup>TH</sup> POLE FOR POWER, ON BACK OF PANEL	<b>DSC040PSR</b>	<b>11.53</b>

N.B.: on request, circuit breakers with a capacity in excess of 40 Ampere are available, in addition to further accessories.

The manoeuvre switches-circuit breakers of the new DS series are characterised by high performance levels, and are intended for installation in distribution and power supply circuits to motors, in panels or directly onboard the machine, with alternating current capacities of 20, 32 and 40 A.

The manoeuvre switches-circuit breakers of the DS series are characterised by outer dimensions that are some of the smallest on the market, and are equipped with a complete range of IP66 finishes, for use even in tight spaces and in difficult applications.