POWER TOOL SWITCHES



		GGER SWITCHES WITH LEVER, SERIES LLA	42	 	ı		
DIMI	ENSIONAL	DIAGRAM	MODEL	DESCRIPTION	CODE	€/pc	
	1	73	ASSEMAN CE THE ASSEMAN TO THE ASSEMANT TO	Two-pole switch, with black lever distance between hole centres 55 mm	LLA422N1	35.95	
;		42 30 30 30 30 30 30 30 30 30 30		Two-pole switch, with orange lever distance between hole centres 55 mm	LLA422A1	33.80	
				Two-pole switch, with black lever, distance between hole cen- tres 65 mm	LLA422N3	34.39	
	1 — 1 2 — 2	12 22 28 27 27 27 27 27 27 27 27 27 27 27 27 27	Tanahaman CE TO	Two-pole switch with unstable lever, without fastening holes, L31	LLA423N0	38.10	
1	112		CE 2500 17-1997	Two-pole switch with unstable black lever, without fastening holes, L41.5	LLA424NO	35.95	
2	-	15.5.5.4 15.5.5.4 15.5.5.4 15.5.5.4 17.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.5.4 18.5.4		Two-pole switch with special lever	LLA424NOA	35.45	
THREE-POLE SWITCHES WITH LEVER DIMENSIONAL DIAGRAM MODEL DESCRIPTION CODE €/pc							
		8.5					

DIMENSIONAL	DIAGRAM	MUDEL	DESCRIPTION	CODE	€/pc
1—————————————————————————————————————	42 33 33 34	LFA203R CE	Three-pole switch with stable lever	LFA203R	35.95
11 22 33	3.3		Three-pole switch with protection, back of panel fas- tening	LFA203RPT	42.39