

MECHANICAL SEALS FOR GRUNDFOS® PUMPS


WIDIA/GRAPHITE/EPDM

LIQUIBLOK
UBE


WIDIA/WIDIA/EPDM

UUE

Rotation: bi directional
 Stationary ring: with O-ring
 Max pressure: 12 bar
 Temperature: -40° +150°
 Use: for superheated water, with presence of abrasives



Dimensions mm					WIDIA/GRAPHITE/EPDM		WIDIA/WIDIA/EPDM	
SHAFT	ROTATING PART		STATIONARY RING		COMPLETE MECHANICAL SEAL		COMPLETE MECHANICAL SEAL	
d1	d3	L	d7	I4	CODE	€	CODE	€
12	22	30	23	7.6	0355012	55.00	0355112	71.30
16	26	30	27	9	0355016	63.00	0355116	98.60



Dimensions mm					WIDIA/GRAPHITE/EPDM		WIDIA/WIDIA/EPDM	
SHAFT	ROTATING PART		STATIONARY RING		COMPLETE MECHANICAL SEAL		COMPLETE MECHANICAL SEAL	
d1	d3	L	d7	I4	CODE	€	CODE	€
22	36	30	37	11	0350022	109.00	0351022	153.00
33	50	35	48	7.5	0350033	119.00	0351033	166.00

Mechanical seals suggested for pump models Style A, Style B, Style C, Style: CHI, CHIE, CRK, SPK, CP, CR, CRN, LM, LP, NM, NP, DNM, DNP, CLM, TP, TPD & AP

RB 24-G6

GRAPHITE/SILICON/EPDM


LIQUIBLOK
BQE

Temperature: -40° max +150°
 Use: superheated water, alcohol, acetate, vapour (no hydrocarbons) with slight presence of abrasives.

WIDIA/WIDIA/EPDM

UUE

Temperature: -40° max +150°
 Use: superheated water, alcohol, acetate (no hydrocarbons) with presence of abrasives.



Rotation: bi directional Stationary ring: with O-ring Max pressure: 10 bar	Dimensions mm					GRAPHITE/SILICON/EPDM		WIDIA/WIDIA/EPDM	
	SHAFT	ROTATING PART		STATIONARY RING		COMPLETE MECHANICAL SEAL		COMPLETE MECHANICAL SEAL	
	d1	d3	L	d7	I4	CODE	€	CODE	€
	28	49	42.5	43	7.5	0324128	128.00	0324228	188.00
	38	58	46	56	9	0324138	174.00	0324238	220.00
	48	70	51	66	9	0324148	236.00	--	--