MECHANICAL SEALS FOR **GRUNDFOS® PUMPS**

SILICON/GRAPHITE/EPDM

LIQUIBLOK

QBE

SILICON/SILICON/EPDM

QQE

WIDIA/WIDIA/EPDM


UUE

Cartridge mechanical seal with screw, alternative to Grundfos® Style H mechanical seal

Max pressure: 10 bar Temperature: -40° +150°

Use: for superheated water, with presence of abrasives





Dimensions mm				SILICON/GRAPHITE/EPDM		SILICON/SILICON/EPDM		WIDIA/WIDIA/EPDM	
SHAFT ROTATING PART		STATIONARY RING	COMPLETE MECHANICAL SEAL		COMPLETE MECHANICAL SEAL		COMPLETE MECHANICAL SEAL		
d1	d3	L	d7	CODE	€	CODE	€	CODE	€
12	25	45	29	0352012	122.00	0353012	124.00		
16	30.5	45	34	0352016	165.00	0353016	171.00	0354016	176.00

Mechanical seals suggested for pump models Style MTR, CR1 3, 5, 10, 15, 20, 32, 45, 64, 90 CRN1 3, 5, 10, 20, 32, 45, 64, 90

WIDIA/GRAPHITE/EPDM

UBE


WIDIA/WIDIA/EPDM

UUE

Cartridge mechanical seal in alternative to the Grundfos® Style E mechanical seal

Max pressure: 10 bar Temperature: -40° +150°

Use: for superheated water, with presence of abrasives



			WIDIA/GF	RAPHITE/	WIDIA/WIDIA/EPDM		
	Dimensions mm		EPDN	I UBE	UUE		
SHAFT	ROTATING PART	STATIONARY RING	COMPLETE MEC	CHANICAL SEAL	COMPLETE MECHANICAL SEAL		
d1	L	d7	CODE	€	CODE	€	
22	50	50	0352022	248.00	0354022	280.00	
		l					

Mechanical seals suggested for pump models Style MTR, CR/CRN 32, CR/CRN 45, CR/CRN 64, CR/CRN 90