

ROTEN 2

STEEL/GRAPHITE/NBR


X1P1G1V1P1 (X6GV6)

 ROTEN®



Rotation: uni directional right
Stationary ring: with O-ring
Max pressure: 12 bar
Temperature: -25° +90°C


Use: water, clean liquids



Dimensions mm

SHAFT d1	ROTATING PART L	STATIONARY RING		COMPLETE MECHANICAL SEAL	STATIONARY RING			
		d7	l4		CODE	€		
6	15	13.1	4.5	1	0101006	21.36	0151006	6.09
7	15	17.1	5.5	1	0101007	21.36	0151007	6.11
8	15	17.1	5.5	1	0101008	21.36	0151008	6.14
9	15	17.1	5.5	1	0101009	21.36	0151009	6.16
10	15	18.1	5.5	6	0101010	12.44	0151010	3.76
11	18	20.6	5.5	6	0101011	23.04	0151011	6.95
12	18	20.6	5.5	12	0101012	12.83	0151012	3.94
13	22	23.1	6	6	0101013	14.33	0151013	4.26
14	22	23.1	6	6	0101014	14.94	0151014	4.26
15	22	26.9	7	6	0101015	15.43	0151015	4.71
16	23	26.9	7	6	0101016	16.37	0151016	4.71
17	23	26.9	7	6	0101017	17.29	0151017	4.71
18	24	30.9	8	6	0101018	18.45	0151018	5.04
19	25	30.9	8	6	0101019	20.19	0151019	5.20
20	25	30.9	8	6	0101020	20.49	0151020	5.20
21	25	35.4	8	6	0101021	25.41	0151021	10.80
22	25	35.4	8	6	0101022	25.57	0151022	6.20
23	27	35.4	8	6	0101023	45.85	0151023	10.87
24	27	35.4	8	6	0101024	26.83	0151024	6.20
25	27	38.2	8.5	6	0101025	33.30	0151025	10.58
26	27	38.2	8.5	1	0101026	34.08	0151026	10.58
27	27	38.2	8.5	1	0101027	34.85	0151027	18.60
28	29	43.3	9	6	0101028	37.73	0151028	14.52
29	30	43.3	9	1	0101029	70.60	0151029	25.57
30	30	43.3	9	6	0101030	41.81	0151030	14.52
31	30	43.3	9	1	0101031	74.26	0151031	25.57

- to place an order for a mechanical seal with left-handed rotation, add SX after the code. For example: 0101028SX (5% increase on the price list)
- packages with stationary ring: individual pieces

 INFO: On pages 12 and 13 there are EPDM and FPM o-rings available.

